



Fork positioner

RZV-G-SF-F
RZV-G-SF-S

integral sideshift, bolt-on forks

The **fork positioner RZV-G** has a stable round bar guide in which the carrier with bolt-on forks is positioned. Integral sideshift enables sideshifting dependent on opening range of the forks. Use of standard forks according to ISO 2328 is also possible.



FrontCam only

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-F*	1600/500	1,0-1,6/500	II	980	470-1040	100x40x1200	126	228	220
RZV 20-G-SF-F*	2000/500	1,8-2,0/500	II	1040	470-1100	100x45x1200	126	221	232
RZV 25-G-SF-F*	2500/500	2,5/500	II	1150	490-1230	120x40x1200	126	215	252
RZV 28-G-SF-F*	2500/600	2,5/600	II	1150	495-1235	125x45x1200	126	225	275
RZV 30-G-SF-F*	3000/500	3,0/500	III	1150	495-1235	125x45x1200	138	205	305
RZV 35-G-SF-F	3500/500	3,0/600- 3,5/500	III	1150	490-1230	140x50x1200	138	222	345
RZV 40-G-SF-F	4000/500	3,5/600- 4,0/500	III	1350	490-1430	140x50x1200	153	225	400
RZV 45-G-SF-F	5000/600	4,0-5/600	III	1350	500-1440	150x60x1200	153	225	450

SideCam only

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-S*	1600/500	1,0-1,6/500	II	980	470-1040	100x40x1200	126	228	220
RZV 20-G-SF-S*	2000/500	1,8-2,0/500	II	1040	470-1100	100x45x1200	126	221	232
RZV 25-G-SF-S*	2500/500	2,5/500	II	1150	490-1230	120x40x1200	126	215	252
RZV 28-G-SF-S*	2500/600	2,5/600	II	1150	495-1235	125x45x1200	126	225	275
RZV 30-G-SF-S*	3000/500	3,0/500	III	1150	495-1235	125x45x1200	138	205	305
RZV 35-G-SF-S	3500/500	3,0/600- 3,5/500	III	1150	490-1230	140x50x1200	138	222	345
RZV 40-G-SF-S	4000/500	3,5/600- 4,0/500	III	1350	490-1430	140x50x1200	153	225	400
RZV 45-G-SF-S	5000/600	4,0-5/600	III	1350	500-1440	150x60x1200	153	225	450

- 2 hydraulic functions required
- includes hoses and couplings
- includes 5-pin M12 transfer connector
- integral sideshift as standard
- features bolt-on forks as standard
- plug and play connection as standard
- 12/24 Volt system

- protection strip with integrated hose guide as standard
- suitable for longer forks
- clamping of goods not allowed
- accessories see page 197

*for forks longer than 1600 mm the cross section might change, please ask

DURWEN
Forklift Attachments

More than 75 years experience