


Revolving fork positioner

360° total rotation, constant sideshift, bolt-on forks

DZVW-GS

The revolving fork positioner DZVW-GS rotates 360° and has bolt-on forks. Rotation, sideshift and fork positioning allow for quick and safe operation. The strong construction with round bars guarantees a long service life. The rotator has a strong direct transmission with proven service in heavy-duty applications. The rotation bearing is protected against dust. The unit is not designed for use with inverted forks. Clamping is not allowed. Suitable solutions upon request.




type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm OTO	forks b x h x L mm	sideshift mm	V LLC mm	ESP COG mm	weight kg
DZVW 16-GS*	1600/500	1,6/500	II	1000	300-880	100x40x1200	+/- 100	249	222	485
DZVW 20-GS*	2000/500	1,8-2,0/500	II	1000	300-880	100x45x1200		249	234	496
DZVW 25-GS*	2500/500	2,0/600 - 2,5/500	II	1150	320-1050	120x40x1200		232	214	565
DZVW 28-GS*	2500/600	2,5 / 600	II	1150	325-1055	125x45x1200		232	229	585
DZVW 30-GS*	3000/500	3,0 / 500	III	1150	325-1055	125x45x1200		247	233	642
DZVW 35-GS	3500/500	3,0 / 600 - 3,5/500	III	1150	340-1070	140x50x1200		247	254	678
DZVW 40-GS	4000/600	3,5/600 - 4,0/600	III	1350	370-1250	140x50x1200		280	232	935
DZVW 45-GS	5000/600	3,5-5,0/600	III	1350	380-1260	150x60x1200		281	255	984
DZVW 50-GS	5000/600	5,0/600	IV	1350	380-1260	150x70x1200		310	258	1215
DZVW 60-GS	6000/600	6,0/600	IV	1420	380-1300	150x70x1200		329	255	1425
DZVW 80-GS	8000/600	7,0-8,0/600	IV	1800	480-1680	200x70x1200		356	297	1771

- 3 hydraulic functions required
- includes hoses and couplings
- constant sideshift as standard
- features bolt-on forks as standard

- pressure relief valve as standard
- standard with protection strip type SB-DG (does not rotate)
- pressure gauge with hand wheel upon request

- solenoid valve upon request (12 V, 24 V, 48 V, 80 V - please specify)
- forks longer than 1800 mm upon request
- clamping of goods is not allowed
- execution without forks not available



***Forks longer 1600 mm
cross section changes**

type	forks b x h mm
DZVW 16-GS	100x50
DZVW 20-GS	100x50
DZVW 25-GS	120x50
DZVW 28-GS	125x50
DZVW 30-GS	125x50

DURWEN
Forklift Attachments

More than 75 years experience