


Fork positioner

PZV-S-TGZ
ISO IV

telescopic forks, constant sideshift

The **sideshifting fork positioner PZV-S-TGZ** uses T profile guides. Compact design offers reliability and excellent operator visibility. The constant sideshift operates at any fork position. The combined telescopic forks support faster and safer work due to ideal support of the transported goods. Single side loading is enabled as well. The forks are positioned hydraulically in your daily operation, however the pre-set position of the forks on the carrier can be changed due to the bolted fork stops. Under the table you find the minimum pre-set position available inside to inside fork shanks.



type	capacity kg/ LC 1 mm	capacity kg/ LC 2 mm	lift truck to/ LC mm	ISO	B mm	A mm	retracted extended L1/L2 mm	fork b x h mm	fork back mm	sideshift mm	V LLC mm	ESP/COG 1/2 mm	weight kg
PZV-S-TGZ.50.1200 PZV-S-TGZ.50.1350	5000/600	2300/1450 1900/1750	5,0/600	IV	1350	500-1440	1200/2050 1350/2350	161x62	150x50	+/- 100	158	284/369 324/429	595 615
PZV-S-TGZ.60.1200	6000/600	3100/1450	6,0/600	IV	1460 1860	575-1575 575-1975	1200/2050	215x69	200x50	+/- 100 +/- 160	166	311/379 268/353	895 960
PZV-S-TGZ.60.1350	6000/600	2570/1750	6,0/600	IV	1460 1860	575-1575 575-1975	1350/2350	215x69	200x50	+/- 100 +/- 160	166	321/445 303/419	925 990

- 3 hydraulic functions required
- includes hoses and couplings
- hook-on TGZ ISO 2328 as standard
- bolt-on forks upon request
(drilling pattern change, please ask)
- protection strip with integrated hose guide as standard
- standard with easily replaceable wear zones and fork tip made of solid steel to reduce service costs

- thicker mangan steel wear zone (+6 mm) ISO IV upon request
- pallet stop ISO IV (see page 198) upon request:
 - A) 75 mm on the fork pocket sides
 - B) 400 mm
 - C) 850 mm
- type B and C reduce the useable length by 50 mm
- different pallet stop positions upon request
- solenoid valve upon request (12 V, 24 V, 48 V, 80 V - please specify)
- for ISO type B mounting ISO IV upon request
- PZV-S-TGZ 50 allow min. fork position 69 mm inside
- PZV-S-TGZ 60 allow min. fork position 145 mm inside



DURWEN 
Forklift Attachments

More than 75 years experience

PL 01-2024