



Sideshifting fork positioner

RZV-GS
ISO IV

constant sideshift, bolt-on forks

The **sideshifting fork positioner RZV-GS** uses stable round bar guides for fork positioning. The simple design offers reliability and excellent operator visibility. The constant sideshift operates at any fork position.





type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	sideshift mm	V LLC mm	ESP COG mm	weight kg
RZV 50-GS	5000/600	5,0/600	IV	1250 1350 1450 1550	500-1340 500-1440 500-1540 500-1640	150x70x1200	+/- 100	180	278 286 278 271	649 661 687 713
RZV 60-GS	6000/600	6,0/600		1360 1460 1600 1660 1860	560-1460 560-1560 560-1700 560-1760 560-1960	150x70x1200	+/- 100 +/- 100 +/- 160 +/- 160 +/- 160	190	186 185 184 183 180	790 805 830 840 870
RZV 70-GS	7000/600	6,5-7,0/600		1460 1860 2060	560-1560 560-1960 560-2160	150x70x1200	+/- 100 +/- 160 +/- 160	190	188 183 180	835 930 980
RZV 80-GS	8000/600	8,0/600		1460 1800 1860 2000 2060 2160 2260 2400	560-1560 560-1900 560-1960 560-2100 560-2160 560-2260 560-2360 560-2500	200x70x1200	+/- 100 +/- 160 +/- 160 +/- 160 +/- 160 +/- 160 +/- 160 +/- 160	190	195 189 189 187 186 185 183 179	915 975 985 995 1010 1035 1060 1110
RZV 100-GS	8000/900	8,0/900		2060 2160 2260 2400	560-2160 560-2260 560-2360 560-2500	200x80x1200	+/- 160	216	180 178 175 172	1230 1260 1285 1340
RZV 110-GS	8000/1100	8,0/1100		2060 2260 2400	560-2160 560-2360 560-2500	200x80x1200	+/- 160	218	190 186 183	1292 1348 1403

- 2 hydraulic functions required
- includes hoses and couplings

- constant sideshift as standard
- features bolt-on forks as standard

- for hook-on forks ISO 2328
- load backrest/protection strip see page 240
- quick release hooks (ISO IV) upon request
- for forks up to 2400 mm, longer please ask
- clamping of goods not allowed

option: protection strip



DURWEN
Forklift Attachments

More than 75 years experience