

Fork positioner

RZV-IG ISO II

integrated, integral sideshift, bolt-on forks

The fork positioner RZV-IG with bolt-on forks has stable round bar guides in which the two mounting plates with forks are moved. Sideshift by valve allows sideshift depending on the opening range of the fork mounts. Standard ISO 2328 forks can also be used and the fork length can be up to 2400 mm. Very good visibility is to be emphasized which makes safe working possible. Euro pallets can be picked up lengthwise. In addition, this device is characterised by its compact design whereby the forklift retains the greatest possible residual load capacity. Delivery incl. brackets, stubshafts and chain anchors.





type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
RZV 16-IG*	1600/500	1,0-1,6/500	II	850 980 1040	470-910 470-1040 470-1100	100x40x1200	- 126	255 250 250	215 225 235
RZV 20-IG*	2000/500	1,8-2,0/500		850 980 1040 1150	470-910 470-1040 470-1100 470-1210	100x45x1200		280 270 265 265	225 240 245 250
RZV 25-IG*	2500/500	2,0/600-2,5/500		980 1040 1150 1350	490-1060 490-1120 490-1230 490-1430	120x40x1200		270 270 270 265	245 255 260 270
RZV 28-1G*	2500/600	2,5/600		1040 1150 1350	495-1125 495-1235 495-1435	125x45x1200		295 290 285	273 280 305

- 2 hydraulic functions required
- without hoses and couplings
- features bolt-on forks as standard
- sideshift via valve, depending on opening range
- for hook-on forks ISO 2328
- including brackets, chain anchor and stub shafts, without rollers
- detailed information including carriage drawings are required with the order as well as fork lift model and most model details
- weight, COG and LLC do not include brackets
- LLC does not include forks
- protection strip/load backrest see page 240
- for forks up to 2400 mm, longer please ask
- clamping of goods is not allowed

*Forks longer 1600 mm
cross section changes

cross section changes					
type	forks b x h				
	mm				
RZV 16-IG	100x50				
RZV 20-IG	100x50				
RZV 25-IG	120x50				
RZV 28-IG	125x50				





option: protection strip

