



Protection strip for DG (P. 227), DG-S (P.1 228)

type	ISO	width B mm	height* H mm	weight kg	included on the following attachments	option available for**
SB-DG 25	II	1000	795	11	DUZ 15, DUZ 15-S, DDGK 20, DPBK 20, DGE 20, DZVW 16-G/GS	DG/DG-S 16, DG/DG-S 20
		1050	880	12	DUZ 25, DUZ 25-S, DDGK 25, DPBK 25, PWK 25, DGE 25, DZVW 25-G/GS	DG/DG-S 25
SB-DG 45	III	1050	880	12	DUZ 30, DUZ 35, DUZ 30-S, DUZ 35-S, DDGK 30, DPBK 30, PWK 30, PWK 35, DGE 30, DZVW 30-G, DZVW 35-G/GS	DG/DG-S 30, DG/DG-S 35
		1275	1000	17	DUZ 40, DUZ 45, DUZ 48, DUZ 40-S, DUZ 45-S, DUZ 48-S, DPBK 35, DPBK 40, DPBK 45, PWK 45, DZVW 45-G/GS	DG/DG-S 45
SB-DG 100	IV	1275	1045	17	DUZ 50, DUZ 50-S, DPBK 50, DZVW 50-G/GS	DG/DG-S 50
		1310	1185	26	DUZ 60, DUZ 80, DUZ 60-S, DUZ 80-S, DPBK 80, DZVW 60-G, DZVW 80-G/GS	DG/DG-S 60, DG/DG-S 80
		1310	1170	26	DUZ 100, DUZ 100-S, DPBK 100	DG/DG-S 100, DG/DG-S 120

- protection strip is mounted to the rotators body, therefore it is not rotating
- other widths upon request

* with ISO 2328 A

** data change, please ask