


Quick-change system


SWV
ISO II/III

manual operation

With the Durwen **quick-change unit SWV**, attachments can be changed quickly and without the use of tools. This device is suitable when the truck is used for a wide range of applications and several attachments are needed. The lower locking mechanism is manually operated as standard. The fork carriage is hooked into the upper mounting of the base frame.



base frame with
manual lock mechanism



base frame with hook-on
fork carriage installed

hook-on fork carriage



quick change unit, hook-on base frame

| type | capacity kg LC mm | lift truck to LC mm | ISO | B mm | ESP COG mm | weight kg |
|---------|-------------------------|---------------------------|-----|---------|------------------|--------------|
| SWV 25 | 2500/600 | 2500/600 | II | 1050 | 30 | 105 |
| SWV 35 | 3500/600 | 3500/600 | III | 1050 | 32 | 175 |
| SWV 45 | 5000/600 | 5000/600 | III | 1050 | 38 | 180 |
| SWV 100 | 8000/900 | 8000/900 | IV | 1100 | 50 | 300 |

single hook-on fork carriage, for additional ISO forks or attachment

| type | ISO | B mm | weight kg |
|---------------------------|-----|---------|--------------|
| fork carriage for SWV 25 | II | 1050 | 65 |
| fork carriage for SWV 35 | III | 1150 | 123 |
| fork carriage for SWV 45 | III | 1350 | 150 |
| fork carriage for SWV 100 | IV | 1800 | 350 |

● hooks can be welded directly on some Durwen attachments for reduced lost load center and higher residual capacity. for SWV 25, SWV 35, SWV 45, SWV 100 upon request, no add-on price for integral attachments - choose from this catalogue.

Option available for: PGK, PBK, PZK, USK, UKK (all), ZVP, RZV, PZV, RZV-TGZ, ZVP-TGZ

technical data quick change unit (base frame) incl. fork carriage with hooks

| type | V LLC mm | ESP COG mm | weight kg |
|-------------------------|----------------|------------------|--------------|
| SWV 25 + fork carriage | 140 | 62 | 170 |
| SWV 35 + fork carriage | 195 | 85 | 298 |
| SWV 45 + fork carriage | 205 | 95 | 330 |
| SWV 100 + fork carriage | 272 | 150 | 650 |

| constant sideshift upon request (requires one additional hydraulic function) | extra weight kg | extra thickness mm |
|---|--------------------|-----------------------|
| constant sideshift ISO II | +20 kg | +17 mm |
| constant sideshift ISO III | +25 kg | +17 mm |
| constant sideshift ISO IV | +85 kg | +23 mm |

- hydraulic locking upon request
- parking devices for attachments upon request
- integral version upon request
- multiple quick coupling upon request

DURWEN 
Forklift Attachments

More than 75 years experience