



Tissue roll clamps TRK 360°

TRK 60-110
ISO IV

The **Durwen tissue roll clamps TRK 360°** are designed with ideal geometry for handling tissue rolls. The large rubber-faced contact plates are carefully designed for good friction coefficient and for minimised impact on tissue at the same time. The 360° rotation is based on the Durwen rotator with drive via worm wheel-worm gear.



type	capacity kg LC mm	ISO	roll diameter min - max mm	short arm	GH mm	contact plates B x L mm	H mm	V LLC mm	ESP COG mm	weight kg
TRK 60 B - 18	3200/915	IV	500 - 1830	powered	1640	400x1600	475/480	240	428	1650
TRK 60 B - 20	2900/1025		600 - 2050						445	1720
TRK 60 B - 21	2750/1075		600 - 2150						462	1750
TRK 60 B - 22	2650/1125		600 - 2250						485	1790
TRK 60 B - 25	2200/1250		600 - 2500						504	2005
TRK 80 B - 20	3200/1025		600 - 2050		1640	400x1600	475/480	240	445	1895
TRK 80 B - 21	3050/1075		600 - 2150						462	1925
TRK 80 B - 22	3050/1125		600 - 2250						485	1965
TRK 80 B - 25	2600/1250		600 - 2500						503	2180
TRK 100 B - 21	3350/1075		800 - 2150		1840	400x1800	550	258	478	1995
TRK 100 B - 23	3250/1175		800 - 2350						495	2065
TRK 100 B - 25	3250/1275		800 - 2550						512	2170
TRK 100 B - 26	2850/1325		800 - 2650						530	2230
TRK 110 B - 26	3800/1300		850 - 2600			550x1800			523	2370

- 2 hydraulic functions required
- includes hoses and couplings
- safety valve as standard
- contact plates with rubber-coating (smooth or rhombic) as standard, optional with PU-coating
- contact plates convex angled outward upon request

- for picking up horizontal rolls min. 5° mast forward tilt required
- powered short arm sequential movement as standard, positioning at 45°, chose on order (no add-on price)
- hydraulic pressure of 160 bar required at forklift truck coupling, less pressure results in less clamping force
- centre cover upon request
- load extender upon request



DURWEN 
Forklift Attachments

More than 75 years experience

PL 01-2024