



# Appliance clamp

**UKK-PE**  
**UKK-PD**


articulating arms, integral sideshift

**The appliance clamp UKK-PE/PD** with articulating arms is designed for the transport of packaged goods without pallets such as domestic appliances. **Type UKK-PE** is equipped with single articulation on both arms.

**Type UKK-PD** has triple articulation on both arms for optimum pressure distribution with split contact plates.



C = wear zone  
approx. 5 mm



PE = both arms with single articulation

| type      | capacity<br>kg<br>LC mm | lift truck<br>to<br>LC mm | ISO    | B<br>mm | A<br>ITI<br>mm | arm length*<br>L<br>mm | arm height<br>H<br>mm | arm<br>thickness T<br>mm | V<br>LLC<br>mm | ESP<br>COG<br>mm | weight<br>kg |
|-----------|-------------------------|---------------------------|--------|---------|----------------|------------------------|-----------------------|--------------------------|----------------|------------------|--------------|
| UKK 15-PE | 1000/600                | 1,5-1,8/500               | II     | 880     | 360-1400       | 1220                   | 1200                  | 60                       | 130            | 450              | 715          |
|           |                         |                           |        | 1050    | 430-1720       | 1220                   |                       |                          |                | 445              | 735          |
|           |                         |                           |        | 1150    | 430-1820       | 1220                   |                       |                          |                | 440              | 750          |
|           |                         |                           |        | 1150    | 430-1820       | 1380                   |                       |                          |                | 465              | 810          |
|           |                         |                           |        | 1250    | 430-1920       | 1220                   |                       |                          |                | 435              | 765          |
| UKK 25-PE | 1300/600                | 2,0-2,5/600               | II     | 1050    | 430-1720       | 1220                   | 1200                  | 60                       | 130            | 440              | 745          |
|           |                         |                           |        | 1150    | 430-1820       | 1220                   |                       |                          |                | 435              | 760          |
|           |                         |                           |        | 1150    | 430-1820       | 1380                   |                       |                          |                | 460              | 820          |
|           |                         |                           |        | 1350    | 430-2020       | 1220                   |                       |                          |                | 430              | 790          |
|           |                         |                           |        | 1350    | 430-2020       | 1380                   |                       |                          |                | 455              | 850          |
| UKK 28-PE | 1600/600                | 2,5-3,0/600               | II/III | 1550    | 430-2220       | 1380                   | 1200                  | 65                       | 140            | 445              | 880          |
|           |                         |                           |        | 1350    | 430-2020       | 1220                   |                       |                          |                | 450              | 925          |
|           |                         |                           |        | 1350    | 560-2210       | 1220                   |                       |                          |                | 450              | 930          |
|           |                         |                           |        | 1450    | 430-2120       | 1220                   |                       |                          |                | 440              | 940          |
|           |                         |                           |        | 1450    | 560-2310       | 1220                   |                       |                          |                | 440              | 945          |
|           |                         |                           |        | 1450    | 430-2120       | 1380                   |                       |                          |                | 460              | 995          |
|           |                         |                           |        | 1450    | 560-2310       | 1380                   |                       |                          |                | 460              | 1000         |
|           |                         |                           |        | 1550    | 430-2220       | 1380                   |                       |                          |                | 455              | 1010         |
|           |                         |                           |        | 1550    | 560-2410       | 1380                   |                       |                          |                | 455              | 1015         |
| UKK 25-PD | 1300/600                | 2,0-2,5/600               | II     | 1750    | 430-2420       | 1380                   | 1200                  | 60                       | 130            | 450              | 1040         |
|           |                         |                           |        | 1750    | 560-2610       | 1380                   |                       |                          |                | 450              | 1045         |

PD = both arms with triple articulation

| type      | capacity<br>kg<br>LC mm | lift truck<br>to<br>LC mm | ISO    | B<br>mm | A<br>ITI<br>mm | arm length*<br>L<br>mm | arm height<br>H<br>mm | arm<br>thickness T<br>mm | V<br>LLC<br>mm | ESP<br>COG<br>mm | weight<br>kg |
|-----------|-------------------------|---------------------------|--------|---------|----------------|------------------------|-----------------------|--------------------------|----------------|------------------|--------------|
| UKK 15-PD | 1000/600                | 1,5-1,8/500               | II     | 1050    | 430-1720       | 1220                   | 1200                  | 60                       | 130            | 445              | 735          |
|           |                         |                           |        | 1150    | 430-1820       | 1220                   |                       |                          |                | 440              | 750          |
|           |                         |                           |        | 1150    | 430-1820       | 1380                   |                       |                          |                | 465              | 810          |
|           |                         |                           |        | 1250    | 430-1920       | 1220                   |                       |                          |                | 435              | 765          |
| UKK 25-PD | 1300/600                | 2,0-2,5/600               | II     | 1050    | 430-1720       | 1220                   | 1200                  | 60                       | 130            | 440              | 745          |
|           |                         |                           |        | 1150    | 430-1820       | 1220                   |                       |                          |                | 435              | 760          |
|           |                         |                           |        | 1150    | 430-1820       | 1380                   |                       |                          |                | 460              | 820          |
|           |                         |                           |        | 1350    | 430-2020       | 1220                   |                       |                          |                | 430              | 790          |
|           |                         |                           |        | 1350    | 430-2020       | 1380                   |                       |                          |                | 455              | 850          |
| UKK 28-PD | 1600/600                | 2,5-3,0/600               | II/III | 1550    | 430-2220       | 1380                   | 1200                  | 65                       | 140            | 445              | 880          |
|           |                         |                           |        | 1550    | 560-2410       | 1380                   |                       |                          |                | 455              | 1015         |

- 2 hydraulic functions required
- includes hoses and couplings
- pressure gauge as standard
- with pressure relief valve on the clamp function as standard
- with protection strip as standard
- supergrip black as standard surface

- other surfaces see page 59
- clamp force options see page 241
- other arm dimensions upon request
- constant sideshift upon request
- for ISO type B mounting upon request

- \* Arm length equals the usable length from the arm tip to the load contact on the clamp body, contact plate length - 20 mm

**DURWEN**  
Forklift Attachments

More than 75 years experience