

## Fork positioner

## ZVP-S-TGZ ISO II

## telescopic forks, constant sideshift

The **ZVP-S-TGZ** is a combination of fork positioner and telescopic forks that enables quick and cost effective loading and stacking especially when loading and unloading from one side of a vehicle. The unit copes with a variety of logistical needs including different pallet sizes and load dimensions. The telescopic forks feature 100% synchronised reach movement for ease of use. As this fork positioner spreads the forks beyond the frame width, it is ideal for handling wide goods and pallets. Clamping not allowed. Fork pockets feature +2mm wear resistant mangan steel wear zone as standard.





type	capacity kg/ LC 1 mm	capacity kg/ LC 2 mm	lift truck to/ LC mm	ISO	B mm	A mm	retracted extended L1/L2 mm	fork b x h mm	fork back mm	sideshift mm	V LLC mm	ESP/COG 1/2 mm	weight kg
ZVP-S-TGZ.22.1200	2000/500	950/1450	1,5- 2,0/500	II	1050 1150	560-1780 560-1880	1200/2050	- 161x57	150x45	+/- 100	148	290/385 285/380	505 520
ZVP-S-TGZ.22.1350	2000/500	810/1750	1,5- 2,0/500		1050 1150	560-1780 560-1880	1350/2350					340/450 335/445	520 535
ZVP-S-TGZ.25.1200	2500/600	1200/1450	2,5/600		1050 1150	560-1780 560-1880	1200/2050					285/380 280/375	510 525
ZVP-S-TGZ.25.1350	2500/600	1000/1750	2,5/600		1050 1150	560-1780 560-1880	1350/2350					335/445 330/440	526 541

- 3 hydraulic functions required
- includes hoses and couplings
- bolt-on TGZ as standard
- protection strip with integrated hose guide as standard
- standard with easily replaceable wear zones and fork tip made of solid steel to reduce service costs
- thicker mangan steel wear zone (+6 mm) ISO II upon request
- pallet stop ISO II (see page 198) upon request:
  - A) 75 mm on the fork pocket sides
  - B) 400 mm
  - C) 850 mm
  - type B and C reduce the useable length by 50 mm
- different pallet stop positions upon request
- solenoid valve upon request (12 V, 24 V, 48 V, 80 V please specify)
- for ISO type B mounting upon request ISO II



