


Fork positioner

integrated version, integral sideshift

The integral fork positioner ZVW-I offers outstanding durability and excellent visibility. The double chrome axis guideways is particularly clean and enables precise fork positioning due to high-quality hydraulics. Standard forks with ISO mounting or bolt-on forks may be used. The integral sideshift operates depending on fork position. This means that only the fork carriers move inside the static frame.



type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm OTO	b mm	V LLC mm	ESP COG mm	weight kg
ZVW 50-I	5000/600	5,0/600	IV	1350 1450 1550	370-1250 370-1350 370-1450	140	133	48	365 380 400
ZVW 60-I	6000/600	6,0/600		1460 1660 1860	380-1340 380-1540 380-1740	150	150	60	450 490 530
ZVW 70-I	7000/600	6,5-7,0/600		1460 1860 2060	380-1340 380-1740 380-1940	150	177	75	560 660 705
ZVW 80-I	8000/600	8,0/600		1800 1860 2060 2160 2260 2400	480-1680 480-1740 480-1940 480-2040 480-2140 480-2280	200	177	76	670 685 735 760 785 820
ZVW 100-I	8000/900	8,0/900		2060 2160 2260 2400	480-1940 480-2040 480-2140 480-2280	200	195	80	955 990 1020 1070
ZVW 110-I	8000/1100	8,0/1100		2060 2260 2400	480-1940 480-2140 480-2280	200	210	85	1045 1115 1170

- 2 hydraulic functions required
- ready to connect, access metric
- includes sideshift via valve, depending on opening range
- for hook-on forks ISO 2328

- bolt-on forks can be used
- forks not included
- please indicate fork width when ordering
- including brackets, chain anchor and stub shafts, without rollers
- detailed information including carriage drawings are required with the order as well as fork lift model and mast model details

- weight, COG and LLC do not include brackets
- LLC does not include forks
- load backrest/protection strip see page 240
- clamping of goods is not allowed

