



Fork positioner for reach trucks

bolt-on forks, no sideshift

RZV-G-SF-F
RZV-G-SF-S
RZV-G-SF-L

The fork positioner **RZV-G-SF** for reach trucks has a stable round bar guide in which the carrier with bolt-on forks is positioned. The frame width is designed in a way that it fits in between the support arms of the reach truck. Use of standard forks according to ISO 2328 is also possible.



FrontCam only

fork positioner for reach truck, no sideshift, bolt-on forks, small frame

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x l mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-F*	1600/500	1,0-1,6/500	II	850	470-830	100x40x1200	126	263	218
RZV 20-G-SF-F*	2000/500	1,8-2,0/500	II	850	470-830	100x45x1200	126	277	230
RZV 25-G-SF-F*	2500/500	2,5/500	II	850	490-850	120x40x1200	126	284	238
RZV 28-G-SF-F*	2500/600	2,5/600	II	850	495-855	125x45x1200	126	304	258

SideCam only

fork positioner for reach truck, no sideshift, bolt-on forks, small frame

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x l mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-S*	1600/500	1,0-1,6/500	II	850	470-830	100x40x1200	126	263	218
RZV 20-G-SF-S*	2000/500	1,8-2,0/500	II	850	470-830	100x45x1200	126	277	230
RZV 25-G-SF-S*	2500/500	2,5/500	II	850	490-850	120x40x1200	126	284	238
RZV 28-G-SF-S*	2500/600	2,5/600	II	850	495-855	125x45x1200	126	304	258

Laser only

fork positioner for reach truck, no sideshift, bolt-on forks, small frame

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x l mm	V LLC mm	ESP COG mm	weight kg
RZV 16-G-SF-L*	1600/500	1,0-1,6/500	II	850	470-830	100x40x1200	126	263	218
RZV 20-G-SF-L*	2000/500	1,8-2,0/500	II	850	470-830	100x45x1200	126	277	230
RZV 25-G-SF-L*	2500/500	2,5/500	II	850	490-850	120x40x1200	126	284	238
RZV 28-G-SF-L*	2500/600	2,5/600	II	850	495-855	125x45x1200	126	304	258

- 1 hydraulic function required (2 hydraulic functions integral sideshift)
- includes hoses and couplings
- includes 5-pin M12 transfer connector
- features bolt-on forks as standard
- plug and play connection as standard

- 12/24 Volt system
- protection strip with integrated hose guide as standard
- clamping of goods not allowed
- spacer kit upon request, explanation see page 188
- integral sideshift upon request
- accessories see page 197

*for forks longer than 1600 mm the cross section might change, please ask

DURWEN
Forklift Attachments

More than 75 years experience