




Fork positioner

ZVW-GS-SF-F
ZVW-GS-SF-S

constant sideshift, bolt-on forks

The fork positioner **ZVW-GS** is shaft-guided and welded as a stable frame. Constant sideshift is possible to use at every fork position. The forks are bolted on this unit. This attachment is also suitable for smaller carriages. Use of standard forks according to ISO 2328 is also possible.



FrontCam only

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	sideshift mm	V LLC mm	ESP COG mm	weight kg
ZVW 16-GS-SF-F*	1600/500	1,0-1,6/500	II	980	300-860	100x40x1200	+/- 100	124	216	283
ZVW 20-GS-SF-F*	2000/500	1,8-2,0/500	II	1040	300-920	100x45x1200	+/- 100	124	227	298
ZVW 25-GS-SF-F*	2500/500	2,5/500	II	1150	320-1050	120x40x1200	+/- 100	124	231	319
ZVW 28-GS-SF-F*	2500/600	3,0/500	II	1150	325-1055	125x45x1200	+/- 100	124	249	339
ZVW 30-GS-SF-F*	3000/500	3,0/500	III	1150	325-1055	125x45x1200	+/- 100	127	241	363
ZVW 35-GS-SF-F	3500/500	3,0/600- 3,5/500	III	1350	340-1270	140x50x1200	+/- 100	127	252	424
ZVW 40-GS-SF-F	4000/500	3,5/600- 4,0/500	III	1350	370-1250	140x50x1200	+/- 100	150	247	504
ZVW 45-GS-SF-F	5000/600	4,0/600- 5,0/600	III	1350	380-1260	150x60x1200	+/- 100	150	261	566

SideCam only

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	sideshift mm	V LLC mm	ESP COG mm	weight kg
ZVW 16-GS-SF-S*	1600/500	1,0-1,6/500	II	980	300-860	100x40x1200	+/- 100	124	216	283
ZVW 20-GS-SF-S*	2000/500	1,8-2,0/500	II	1040	300-920	100x45x1200	+/- 100	124	227	298
ZVW 25-GS-SF-S*	2500/500	2,5/500	II	1150	320-1050	120x40x1200	+/- 100	124	231	319
ZVW 28-GS-SF-S*	2500/600	3,0/500	II	1150	325-1055	125x45x1200	+/- 100	124	249	339
ZVW 30-GS-SF-S*	3000/500	3,0/500	III	1150	325-1055	125x45x1200	+/- 100	127	241	363
ZVW 35-GS-SF-S	3500/500	3,0/600- 3,5/500	III	1350	340-1270	140x50x1200	+/- 100	127	252	424
ZVW 40-GS-SF-S	4000/500	3,5/600- 4,0/500	III	1350	370-1250	140x50x1200	+/- 100	150	247	504
ZVW 45-GS-SF-S	5000/600	4,0/600- 5,0/600	III	1350	380-1260	150x60x1200	+/- 100	150	261	566

- 2 hydraulic functions required
- includes hoses and couplings
- includes 5-pin M12 transfer connector
- constant sideshift as standard
- features bolt-on forks as standard
- plug and play connection as standard
- 12/24 Volt system

- protection strip with integrated hose guide as standard
- suitable for longer forks
- clamping of goods not allowed
- accessories see page 197

*for forks longer than 1600 mm the cross section might change, please ask

DURWEN
Forklift Attachments

More than 75 years experience