



Fork positioner

ZVW-G-SF-S-L-SE
ZVW-G-SF-PC

integral sideshift, bolt-on forks

The **fork positioner ZVW-G** is shaft-guided and welded as a stable frame. Integral sideshift enables sideshifting dependent on opening range of the forks. The forks are bolted on this unit. This attachment is also suitable for smaller carriages. Use of standard forks according to ISO 2328 is also possible.



SideCam + Laser + Secure

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
ZVW 16-G-SF-S-L-SE*	1600/500	1,0-1,6/500	II	980	300-860	100x40x1200	107	232	240
ZVW 20-G-SF-S-L-SE*	2000/500	1,8-2,0/500	II	1040	300-920	100x45x1200	107	245	257
ZVW 25-G-SF-S-L-SE*	2500/500	2,5/500	II	1150	320-1050	120x40x1200	107	250	275
ZVW 28-G-SF-S-L-SE*	2500/600	2,5/600	II	1150	325-1055	125x45x1200	107	268	295
ZVW 30-G-SF-S-L-SE*	3000/500	3,0/500	III	1150	325-1055	125x45x1200	110	243	338
ZVW 35-G-SF-S-L-SE	3500/500	3,0/600-3,5/500	III	1150	340-1070	140x50x1200	110	268	373
ZVW 40-G-SF-S-L-SE	4000/500	3,5/600-4,0/500	III	1350	370-1250	140x50x1200	133	246	477
ZVW 45-G-SF-S-L-SE	5000/600	4,0/600-5,0/600	III	1350	380-1260	150x60x1200	133	263	528

PremiumCam (FrontCam + SideCam)

type	capacity kg LC mm	lift truck to LC mm	ISO	B mm	A mm	forks b x h x L mm	V LLC mm	ESP COG mm	weight kg
ZVW 16-G-SF-PC*	1600/500	1,0-1,6/500	II	980	300-860	100x40x1200	107	232	240
ZVW 20-G-SF-PC*	2000/500	1,8-2,0/500	II	1040	300-920	100x45x1200	107	245	257
ZVW 25-G-SF-PC*	2500/500	2,5/500	II	1150	320-1050	120x40x1200	107	250	275
ZVW 28-G-SF-PC*	2500/600	2,5/600	II	1150	325-1055	125x45x1200	107	268	295
ZVW 30-G-SF-PC*	3000/500	3,0/500	III	1150	325-1055	125x45x1200	110	243	338
ZVW 35-G-SF-PC	3500/500	3,0/600-3,5/500	III	1150	340-1070	140x50x1200	110	268	373
ZVW 40-G-SF-PC	4000/500	3,5/600-4,0/500	III	1350	370-1250	140x50x1200	133	246	477
ZVW 45-G-SF-PC	5000/600	4,0/600-5,0/600	III	1350	380-1260	150x60x1200	133	263	528

- 2 hydraulic functions required
- includes hoses and couplings
- includes 5-pin M12 transfer connector
- integral sideshift as standard
- features bolt-on forks as standard
- plug and play connection as standard
- 12/24 Volt system

- protection strip with integrated hose guide as standard
- suitable for longer forks
- clamping of goods not allowed
- accessories see page 197

*for forks longer than 1600 mm the cross section might change, please ask

DURWEN
Forklift Attachments

More than 75 years experience